


EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.0V I:3.571A P:800.0W PF:0.974 Freq:50.00Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:120114x1 lm		
NAME: SP04-800-5770-F04006Z	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 150.14 lm/W			
MODEL	5050	Imax (cd)	119429	S/MH (C0/180)	0.93
NOMINAL POWER (W)	/	LOR (%)	100.0	S/MH (C90/270)	0.93
RATED VOLTAGE (V)	/	TOTAL FLUX (lm)	120114	η UP,DN (C0-180)	0.0,50.1
NOMINAL FLUX (lm)	120114	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,49.9
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE (V)	/	η down (%)	100.0	CIBSE SHR MAX	0.95

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:LYJ
Test Date:2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity:65.0%
Test Distance:26.000m [K=0.4548]
Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1148	1146	1138	1129	1130	1129	1138	1146	0- 10	11125	11125	9.26,9.26
20	1007	992.6	981.5	965.0	978.3	965.0	981.5	992.6	10- 20	30126	41252	34.3,34.3
30	700.9	682.7	661.2	647.7	660.6	647.7	661.2	682.7	20- 30	38754	80005	66.6,66.6
40	220.2	209.0	197.7	193.2	199.7	193.2	197.7	209.0	30- 40	26245	106250	88.5,88.5
50	58.38	48.58	57.59	47.82	59.69	47.82	57.59	48.58	40- 50	7007	113257	94.3,94.3
60	32.17	32.60	27.88	32.58	30.59	32.58	27.88	32.60	50- 60	3512	116769	97.2,97.2
70	15.02	16.11	12.73	15.34	14.39	15.34	12.73	16.11	60- 70	2260	119029	99.1,99.1
80	4.426	3.771	3.192	3.493	3.988	3.493	3.192	3.771	70- 80	941.2	119970	99.9,99.9
90	0.0665	0.0404	0.0192	0.0241	0.0271	0.0241	0.0192	0.0404	80- 90	144.0	120114	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:X100cd									UNIT:lm		

Conical surface Flux(90deg): 1.1097e+005 lm

%lum = 92.4%

%lamp = 92.4%

Conical surface Flux(120deg): 1.1677e+005 lm


%lum = 97.2%

%lamp = 97.2%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:LYJ
Test Date:2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity:65.0%
Test Distance:26.000m [K=0.4548]
Remarks:

LUMINANCE LIMITATION CURVES



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	11116	6542
80	19061	13711
75	26756	21466
70	32831	27759
65	42067	35603
60	48114	41586
55	61039	51919
50	67910	66828
45	84577	74482

C Range: 0 - 360DEG

C Interval: 22.5DEG

Test Speed: HIGH

Temperature:25.3℃

Operators:LYJ

Test Date:2022-10-26

γ Range: 0 - 90DEG

γ Interval: 0.5DEG

Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465

Humidity:65.0%


Test Distance:26.000m [K=0.4548]

Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.10	1.07	1.05	1.08	1.05	1.03	1.04	1.02	1.00	1.00	.99	.97	.97	.95	.94	.93
2.0	1.02	.97	.94	.90	.96	.93	.97	.93	.91	.94	.91	.89	.91	.89	.87	.85
3.0	.94	.89	.85	.93	.88	.84	.90	.86	.83	.88	.84	.81	.85	.83	.80	.78
4.0	.88	.82	.77	.86	.81	.77	.84	.80	.76	.82	.78	.75	.80	.77	.74	.72
5.0	.82	.75	.71	.81	.75	.71	.79	.74	.70	.77	.73	.69	.76	.72	.69	.67
6.0	.76	.70	.65	.75	.70	.65	.74	.69	.65	.73	.68	.64	.71	.67	.64	.62
7.0	.71	.65	.61	.71	.65	.61	.69	.64	.60	.68	.63	.60	.67	.63	.60	.58
8.0	.67	.61	.57	.67	.61	.56	.65	.60	.56	.64	.60	.56	.63	.59	.56	.54
9.0	.63	.57	.53	.63	.57	.53	.62	.56	.53	.61	.56	.52	.60	.55	.52	.51
10.0	.60	.54	.50	.59	.53	.49	.58	.53	.49	.58	.53	.49	.57	.52	.49	.48



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:LYJ
 Test Date:2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
 Humidity:65.0%
 Test Distance:26.000m [K=0.4548]
 Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

WEC AND CCEC

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.191	.109	.034	.185	.105	.033	.172	.099	.032	.160	.093	.030	.150	.087	.028		
2.0	.184	.101	.031	.178	.098	.030	.167	.093	.029	.157	.088	.028	.148	.084	.026		
3.0	.175	.093	.028	.170	.091	.027	.161	.087	.026	.152	.083	.026	.144	.080	.025		
4.0	.166	.086	.025	.162	.085	.025	.154	.081	.024	.146	.078	.024	.139	.076	.023		
5.0	.157	.080	.023	.154	.079	.023	.147	.076	.022	.140	.074	.022	.134	.072	.022		
6.0	.150	.075	.021	.147	.074	.021	.140	.072	.021	.135	.070	.021	.129	.068	.020		
7.0	.143	.071	.020	.140	.070	.020	.134	.068	.020	.129	.066	.019	.124	.065	.019		
8.0	.136	.067	.019	.134	.066	.019	.129	.064	.018	.124	.063	.018	.120	.062	.018		
9.0	.130	.063	.018	.128	.062	.017	.123	.061	.017	.119	.060	.017	.115	.059	.017		
10.0	.125	.060	.017	.122	.059	.017	.119	.058	.016	.115	.057	.016	.111	.056	.016		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.172	.157	.144	.147	.135	.124	.101	.093	.086	.058	.054	.050	.019	.017	.016	
2.0	.158	.132	.111	.135	.114	.096	.093	.079	.067	.053	.046	.039	.017	.015	.013	
3.0	.146	.114	.088	.125	.098	.076	.086	.068	.053	.050	.040	.031	.016	.013	.010	
4.0	.136	.099	.071	.117	.086	.061	.080	.060	.043	.047	.035	.026	.015	.011	.008	
5.0	.128	.088	.058	.110	.076	.050	.076	.053	.036	.044	.031	.021	.014	.010	.007	
6.0	.121	.079	.048	.104	.068	.042	.072	.048	.030	.041	.028	.018	.013	.009	.006	
7.0	.114	.071	.041	.098	.062	.036	.068	.043	.025	.039	.025	.015	.013	.008	.005	
8.0	.109	.065	.035	.093	.056	.031	.065	.040	.022	.038	.023	.013	.012	.008	.004	
9.0	.103	.060	.030	.089	.052	.026	.062	.036	.019	.036	.022	.011	.012	.007	.004	
10.0	.099	.055	.027	.085	.048	.023	.059	.034	.017	.034	.020	.010	.011	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3℃
 Operators:LYJ
 Test Date:2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
 Humidity:65.0%
 Test Distance:26.000m [K=0.4548]
 Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	20.3	21.3	20.7	21.7	22.0	19.8	20.8	20.2	21.2	21.5
3H	21.5	22.5	21.9	22.8	23.2	20.8	21.8	21.2	22.1	22.5
4H	21.9	22.8	22.3	23.1	23.5	21.1	22.0	21.5	22.3	22.7
6H	22.1	22.9	22.5	23.3	23.7	21.2	22.0	21.6	22.4	22.8
8H	22.1	22.8	22.5	23.2	23.7	21.2	21.9	21.6	22.3	22.7
12H	22.1	22.8	22.5	23.2	23.6	21.2	21.9	21.6	22.2	22.7
4H 2H	20.8	21.6	21.2	22.0	22.4	20.4	21.2	20.8	21.6	22.0
3H	22.2	22.9	22.6	23.3	23.7	21.6	22.3	22.0	22.7	23.1
4H	22.7	23.3	23.1	23.7	24.1	21.9	22.5	22.4	23.0	23.4
6H	22.9	23.4	23.4	23.9	24.3	22.1	22.6	22.5	23.0	23.5
8H	22.9	23.4	23.4	23.9	24.3	22.0	22.5	22.5	23.0	23.5
12H	22.9	23.3	23.4	23.8	24.3	22.0	22.4	22.5	22.9	23.4
8H 4H	22.7	23.2	23.1	23.6	24.1	22.0	22.5	22.4	22.9	23.4
6H	23.0	23.4	23.5	23.9	24.4	22.1	22.5	22.7	23.0	23.5
8H	23.0	23.4	23.5	23.9	24.4	22.2	22.5	22.7	23.0	23.5
12H	23.0	23.3	23.5	23.8	24.4	22.1	22.4	22.7	22.9	23.5
12H 4H	22.6	23.1	23.1	23.5	24.0	21.9	22.4	22.4	22.9	23.3
6H	22.9	23.3	23.5	23.8	24.3	22.1	22.5	22.7	22.9	23.5
8H	23.0	23.3	23.5	23.8	24.4	22.1	22.4	22.7	22.9	23.5
CIE190: 2010										

CIE190: 2010
Area: 0.13398 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:LYJ
Test Date:2022-10-26

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity:65.0%
Test Distance:26.000m [K=0.4548]
Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT


UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	84	77	73	84	77	73	83	77	73	69
0.80	92	86	82	91	85	81	90	85	81	77
1.00	97	91	87	96	90	87	94	90	86	82
1.25	101	96	92	100	95	91	98	94	91	86
1.50	104	99	95	103	98	95	101	97	94	89
2.00	107	103	99	106	102	98	103	100	97	92
2.50	109	105	102	108	104	101	104	101	99	93
3.00	111	107	104	109	106	103	106	103	101	94
4.00	113	110	108	111	108	106	107	105	104	96
5.00	114	112	110	112	110	108	108	107	105	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004						Suspended			SHRNOM = 1.25	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators: LYJ
 Test Date: 2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.465
 Humidity: 65.0%
 Test Distance: 26.000m [K=0.4548]
 Remarks:


ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:LYJ
Test Date:2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity:65.0%
Test Distance:26.000m [K=0.4548]
Remarks:

AAI Figure




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators: LYJ
Test Date: 2022-10-26

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity: 65.0%
Test Distance: 26.000m [K=0.4548]
Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT


ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators: LYJ
Test Date: 2022-10-26

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity: 65.0%
Test Distance: 26.000m [K=0.4548]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators: LYJ
Test Date: 2022-10-26

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.465
Humidity: 65.0%
Test Distance: 26.000m [K=0.4548]
Remarks: