


## EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.0V I:1.070A P:240.0W PF:0.975 Freq:50.01Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:46396x1 lm		
NAME: LHB09-240H-5070-L03902	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 193.32 lm/W			
MODEL	/	Imax (cd)	31413	S/MH (C0/180)	1.14
NOMINAL POWER (W)	/	LOR (%)	100.0	S/MH (C90/270)	1.15
RATED VOLTAGE (V)	/	TOTAL FLUX (lm)	46396	$\eta$ UP,DN (C0-180)	0.0,50.0
NOMINAL FLUX (lm)	46396	CIE CLASS	DIRECT	$\eta$ UP,DN (C180-360)	0.0,50.0
LAMPS INSIDE	1	$\eta$ up (%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE (V)	/	$\eta$ down (%)	100.0	CIBSE SHR MAX	1.15

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:LYJ  
Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	3119	3124	3126	3124	3119	3124	3126	3124	0- 10	2975	2975	6.41,6.41
20	3087	3110	3095	3110	3087	3110	3095	3110	10- 20	8859	11834	25.5,25.5
30	2656	2695	2668	2695	2656	2695	2668	2695	20- 30	13584	25418	54.8,54.8
40	1476	1447	1474	1447	1476	1447	1474	1447	30- 40	13112	38530	83,83
50	180.6	182.8	194.1	182.8	180.6	182.8	194.1	182.8	40- 50	5647	44177	95.2,95.2
60	90.95	76.63	80.92	76.63	90.95	76.63	80.92	76.63	50- 60	991.8	45168	97.4,97.4
70	75.66	42.74	60.02	42.74	75.66	42.74	60.02	42.74	60- 70	640.3	45809	98.7,98.7
80	39.75	27.03	21.96	27.03	39.75	27.03	21.96	27.03	70- 80	437.2	46246	99.7,99.7
90	1.283	0.6473	1.100	0.6473	1.283	0.6473	1.100	0.6473	80- 90	150.0	46396	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:X10cd									UNIT:lm		

Conical surface Flux(90deg): 42578 lm

%lum = 91.8%

%lamp = 91.8%

Conical surface Flux(120deg): 45168 lm


%lum = 97.4%

%lamp = 97.4%

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:LYJ  
Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:

LUMINANCE LIMITATION CURVES




C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3℃  
Operators:LYJ  
Test Date:2023-03-17

γ Range: 0 - 90DEG  
γ Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3°C  
 Operators:LYJ  
 Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
 Humidity:65.0%  
 Test Distance:26.000m [K=0.4556]  
 Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## WEC AND CCEC

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.204	.116	.037	.197	.113	.036	.185	.106	.034	.173	.100	.032	.162	.094	.030	
2.0	.196	.108	.033	.190	.105	.032	.180	.100	.031	.170	.095	.030	.160	.091	.029	
3.0	.187	.100	.030	.182	.098	.029	.173	.094	.028	.164	.090	.028	.156	.086	.027	
4.0	.178	.092	.027	.174	.091	.027	.165	.088	.026	.158	.085	.026	.151	.082	.025	
5.0	.169	.086	.025	.166	.085	.025	.158	.082	.024	.152	.080	.024	.145	.078	.023	
6.0	.161	.081	.023	.158	.080	.023	.152	.078	.023	.146	.076	.022	.140	.074	.022	
7.0	.154	.076	.022	.151	.075	.021	.145	.073	.021	.140	.072	.021	.135	.070	.021	
8.0	.147	.072	.020	.144	.071	.020	.139	.069	.020	.134	.068	.020	.130	.067	.019	
9.0	.140	.068	.019	.138	.067	.019	.133	.066	.019	.129	.065	.018	.125	.063	.018	
10.0	.134	.064	.018	.132	.064	.018	.128	.063	.018	.124	.061	.017	.120	.060	.017	

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.173	.157	.143	.148	.135	.123	.101	.093	.085	.058	.054	.049	.019	.017	.016	
2.0	.160	.132	.110	.137	.114	.095	.094	.079	.066	.054	.046	.039	.017	.015	.013	
3.0	.149	.114	.086	.127	.098	.075	.087	.068	.052	.050	.040	.031	.016	.013	.010	
4.0	.139	.099	.069	.120	.086	.060	.082	.060	.042	.048	.035	.025	.015	.011	.008	
5.0	.131	.088	.056	.113	.076	.049	.078	.053	.035	.045	.031	.020	.015	.010	.007	
6.0	.124	.079	.047	.107	.069	.041	.074	.048	.029	.043	.028	.017	.014	.009	.006	
7.0	.118	.072	.039	.102	.062	.034	.070	.044	.024	.041	.026	.014	.013	.008	.005	
8.0	.113	.066	.034	.097	.057	.029	.067	.040	.021	.039	.024	.012	.013	.008	.004	
9.0	.108	.061	.029	.093	.053	.025	.064	.037	.018	.037	.022	.011	.012	.007	.004	
10.0	.103	.057	.026	.089	.049	.022	.062	.035	.016	.036	.020	.009	.012	.007	.003	

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3℃  
 Operators:LYJ  
 Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
 Humidity:65.0%  
 Test Distance:26.000m [K=0.4556]  
 Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.3	13.6	13.3	13.9	14.2	13.3	13.5	13.3	13.8	14.1
3H	14.9	15.9	15.3	16.2	16.6	14.2	15.2	14.6	15.5	15.9
4H	16.1	17.0	16.5	17.4	17.8	15.1	16.1	15.5	16.4	16.8
6H	17.0	17.8	17.4	18.2	18.6	15.7	16.5	16.1	16.9	17.3
8H	17.4	18.2	17.8	18.6	19.0	15.8	16.6	16.2	17.0	17.4
12H	18.0	18.7	18.4	19.1	19.5	15.9	16.7	16.4	17.1	17.5
4H 2H	13.3	13.7	13.3	14.1	14.5	13.3	13.7	13.3	14.0	14.4
3H	15.3	16.1	15.7	16.5	16.9	14.8	15.5	15.2	15.9	16.3
4H	16.7	17.3	17.1	17.7	18.2	15.8	16.5	16.3	16.9	17.3
6H	17.7	18.2	18.1	18.7	19.2	16.5	17.1	17.0	17.5	18.0
8H	18.2	18.7	18.6	19.1	19.6	16.6	17.2	17.1	17.6	18.1
12H	18.8	19.3	19.3	19.7	20.2	16.8	17.3	17.3	17.8	18.3
8H 4H	16.8	17.3	17.3	17.8	18.3	16.1	16.6	16.5	17.1	17.5
6H	18.0	18.4	18.5	18.9	19.4	16.9	17.3	17.4	17.9	18.3
8H	18.5	18.9	19.1	19.4	19.9	17.2	17.5	17.7	18.1	18.5
12H	19.2	19.6	19.8	20.1	20.6	17.4	17.7	17.9	18.2	18.8
12H 4H	16.8	17.3	17.3	17.8	18.3	16.1	16.6	16.6	17.1	17.5
6H	18.0	18.4	18.5	18.9	19.4	17.0	17.4	17.5	17.9	18.4
8H	18.6	19.0	19.1	19.5	20.0	17.3	17.6	17.8	18.1	18.7
CIE190: 2010										

CIE190: 2010  
Area: 0.221 m2

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:LYJ  
Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT


## UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	81	74	69	80	73	69	80	73	69	65
0.80	89	82	78	89	82	78	87	81	77	73
1.00	95	88	84	94	88	84	92	88	83	79
1.25	100	94	89	99	93	89	96	92	88	84
1.50	103	97	93	102	96	93	99	95	92	87
2.00	106	101	98	105	100	97	102	98	96	90
2.50	108	104	100	107	103	100	103	100	98	91
3.00	110	106	103	108	105	102	105	102	100	93
4.00	112	109	107	110	108	105	107	104	102	95
5.00	114	111	109	112	109	107	108	106	104	96
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004				Suspended				SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3°C  
 Operators: LYJ  
 Test Date: 2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
 Humidity: 65.0%  
 Test Distance: 26.000m [K=0.4556]  
 Remarks:

## ISOCANDELA DIAGRAM




C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:LYJ  
Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:



## AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:LYJ  
Test Date:2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity:65.0%  
Test Distance:26.000m [K=0.4556]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT


## ISOLUX DIAGRAM



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3°C  
Operators: LYJ  
Test Date: 2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity: 65.0%  
Test Distance: 26.000m [K=0.4556]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3°C  
Operators: LYJ  
Test Date: 2023-03-17

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.00.465  
Humidity: 65.0%  
Test Distance: 26.000m [K=0.4556]  
Remarks: